

IMPACT WRENCH



IMPACT WRENCH

IMPACT WRENCH

Mini Air Ratchet Wrench

1/4"
3/8"



Air Ratchet Wrench

3/8"
1/2"



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed	AVG. Air Consumption		Overall length		Air Inlet	Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	P.T	kg	lb	
MBAS14	1/4"	41	30	300	127.35	4.5	144	5.7	1/4"	0.5	1.1	Rear
MBAS38	3/8"	41	30	300	127.35	4.5	144	5.7	1/4"	0.5	1.1	Rear
MBAA38	3/8"	81	60	160	141.50	5	265	10.4	1/4"	1.2	2.64	Rear
MBAA12	1/2"	81	60	160	141.50	5	265	10.4	1/4"	1.2	2.64	Rear

1/2"

MAGW12



1/2"

MAFR12



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed	AVG. Air Consumption		Overall length		Air Inlet	Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	P.T	kg	lb	
MAGW12	1/2"	270	200	8500	240.55	8.5	155	6.1	1/4"	2	4.4	Rear
MAFR12	1/2"	560	413	6000	325.45	11.5	180	7.1	1/4"	2.54	5.6	Side

IMPACT WRENCH

1/2"



MAJS12



MACS12



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed		AVG. Air Consumption		Overall length		Air Inlet		Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	P.T	kg	lb			
MAJS12	1/2"	542	400	11000	198.10	7	142	5.6	1/4"	1.5	3.3	Handle		
MACS12	1/2"	380	280	10000	113.20	4	143	5.6	1/4"	1.3	2.9	Handle		

1/2"
3/4"



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed		AVG. Air Consumption		Overall length		Air Inlet		Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	P.T	kg	lb			
MACA12	1/2"	1112	820	8500	138.67	4.9	195	7.7	1/4"	2.1	4.6	Handle		
MACA34	3/4"	1112	820	8500	138.67	4.9	195	7.7	1/4"	2.3	4.6	Handle		

1/2"



MABV12



MAEV12



MABA12



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed		AVG. Air Consumption		Overall length		Air Inlet		Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	P.T	kg	lb			
MABA12	1/2"	610	450	7500	138.67	4.9	188	7.4	1/4"	2.60	5.7	Handle		
MAEV12	1/2"	601	443	6700	297.15	10.5	190	7.5	1/4"	2.68	5.9	Handle		
MABV12	1/2"	814	600	7500	124.52	4.4	195	7.7	1/4"	2.86	6.3	Handle		

IMPACT WRENCH

3/4"



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed	AVG. Air Consumption		Overall length		Driver anvil length	Air Inlet	Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	inch	P.T	kg	lb	
MAKA34	3/4"	1000-1300	730-950	4300	424	15	348	13.7	1/2"	3/8"	5.1	11.2	Side
MAKX34	3/4"	1000-1300	730-950	4300	424	15	393	15.5	2-1/4"	3/8"	5.25	11.6	Side

1"



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed	AVG. Air Consumption		Overall length		Driver anvil length	Air Inlet	Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	inch	P.T	kg	lb	
MADA10	1"	1800-2000	1320-1470	4000	424	15	350	13.8	1/2"	3/8"	6.6	14.5	Side
MADT10	1"	1800-2000	1320-1470	4000	424	15	500	19.7	6-1/2"	3/8"	7.4	16.3	Side

1"



Air pressure at 90psi, 6.2bar,

Item No	Square Driver	Max Torque		Free Speed	AVG. Air Consumption		Overall length		Driver anvil length	Air Inlet	Weight		Exhaust
		Nm	ft-lb	rpm	l/min	cfm	mm	inch	inch	P.T	kg	lb	
MAHA10	1"	2500-2900	1840-2130	2800	452	16	393	15.5	1/2"	3/8"	10.3	22.7	Side
MAHT10	1"	2500-2900	1840-2130	2800	452	16	543	21.4	6-1/2"	3/8"	12.3	27.1	Side